

MAN Truck & Bus SE



Scope of delivery

Basic data

Order number: 601764473
Vehicle number: 92S0423
Vehicle variant: TGS 35.400 8X4-4 BL
Basic vehicle: L92S KG 03
Status: Ready for delivery
Planned delivery date: 23.11.2010
Change stop:

VIN: WMA92SZZ5BL061881
Engine number: 50527401092746

Weights

Gross weight: 32000 / 35000 /
1. Front axle: 9000 / 9000 /
2. Front axle: 0 / 0 /
3. Front axle: 0 / 0 /
Leading axle: 0 / 0 /
1. Rear axle: 9500 / 9500 /
2. Rear axle: 9500 / 9500 /
Trailing axle: 9000 / 9000 /

Add/remove	Code	Description
------------	------	-------------

Current scope of delivery

001AA	steering arrangement, left
005U2	Wheelbase 3900+1350+1450 mm
006L0	rear frame overhang 2000 mm
018JB	Engine D2066LF41 - 400 hp / 294 KW EURO5 SCR - 1900 Nm C-R OBD2
021GP	Gearbox software MAN TipMatic® Profi (road deployment)
022GL	MAN TipMatic® 12 21 DD gearbox
023JU	Fuel tank, aluminium 600l right and 35l AdBlue
025MH	front axle VOK-09 dropped
026EF	front springs parabolic 9,5 t
027AN	radiator and intercooler for up to 35 degrees ambient temperature
028AM	air suspension rear
02AAB	instrument panel kmh 'Base-Line'
030EE	steering wheel with height and inclination adjustment
032AB	MAN BrakeMatic (electronic brake system)
034NM	hypoid rear axle HYD-1370/HY-1350
035EX	Hypoid axle ratio i = 3.08
037AC	with differential lock in rear axle
038DH	disc wheels 10-hole 11.75-22.5 on trailing axle
038GH	disc wheels 10 hole 11.75-22.5 on 1st FA TL
038PG	disc wheels 10-hole 9.00-22.5 on 1st RA TL
038RG	disc wheels 10-hole 9.00-22.5 on 2nd RA TL
038TG	disc wheel 10-hole 9.00-22.5 as spare wheel TL

Add/remove	Code	Description
	03KAA	fuel tank fitted
	041AH	trailing axle NOL-09 steered, lifting
	042DF	Digital tachograph, made by CONTI
	045CA	MAN EasyStart for TipMatic
	050NN	M cab 2240mm wide, 1880mm long
	052XA	without stowage boxes
	058BC	seat coverings in high-comfort quality
	058NR	Air-sprung comfort driver's seat, with lumbar support, shoulder adjustment and heating
	059NA	co-driver's seat static, with longitudinal + seat back adjustment
	05NAE	front panel unlockable from inside
	080AE	door interior panelling washable
	116AE	visco fan
	118MA	EDC engine regulation
	119EH	General PTO parameterisation
	122D8	PTO NH/4C without flange f=1.05 right lateral horizontal
	124AL	fuel filter
	124AR	additional fuel filter heated with water trap, make SEPAR
	124EA	fuel filter heating
	128EC	Pressure sensor for air spring bellows
	142AF	calibrate tachograph
	153KC	air conditioning system AC R134A with automatic temperature control without CFHC
	159XS	without cab insulation NORDIC (against cold) for M, L and LX cab
	194AE	operator's manual in DUTCH
	201AS	air intake raised with dry air filter
	201FA	fine dust and pollen filter
	203ER	Control module for external data exchange (customer-specific control module) with body functionality
	205AN	air compressor 1-cylinder, 360 ccm
	206ET	exhaust on lh side with tail pipe towards rear
	208AL	regulated rocker arm brake (EVBeC)
	210AA	flame starting system
	211FF	single-plate clutch MFZ 430
	227AC	rear axle breather upswept
	230ER	front underride guard
	230XX	Without rear underride guard
	230YX	Without lateral underride guard
	232HA	synthetic bumper with integrated airdam
	234KP	trailer coupling ROCKINGER 400G150A

Add/remove	Code	Description
	236AF	cross member for trailer coupling
	241AC	without platform mounting brackets
	245XX	without spare wheel holder
	256AF	steering wheel lock with immobiliser
	256EA	emergency steering pump
	257LM	multifunction steering wheel for 'M' cab
	258HA	anti-lock braking system (ABS)
	258NA	ECAS air suspension
	259CA	disc brake for front axle
	259CB	disc brake for rear axle
	262AC	brake connection 2-line
	263AF	asbestos-free brake linings
	272FA	Entry lighting for driver and co-driver
	276AC	Armrests for driver's seat
	280AC	wiring for tank truck to ADR
	280EC	Fly mesh guard before radiator
	280HT	Engine start/stop device on Engine
	281SC	Driving height raised by 30 mm for roll-off skip loader
	283FM	Air sprung cab mounts for 'M' cab
	303AA	Lockable tank cap - 1 u. non-ventilated (not eligible for approval/registration according to ECE-R34)
	303CC	AdBlue lockable filler cap 1 pc.
	309AA	Beam throw regulator
	310CN	High-beam headlights and fog lights, also with cornering light
	310EE	Halogen twin headlights H7 for right-hand traffic
	310FA	2 spotlights on cab roof
	311PE	Automatic lowering of the air suspension to rubber/metal buffer with residual pressure control
	318AA	marker lamps
	318AK	lateral marker lights
	319AR	reading lamp for driver
	320AC	Switches and wiring for cargo space lighting
	321EC	Central locking
	321EH	Remote control for central locking
	324AC	Two-tone horn,electric
	324CA	Two compressed air horns on the cab roof/roof spoiler
	325AA	MAN Tronic (on-board computer)
	325EK	Language 1 'Dutch' for display in instrument panel
	325FE	Language 2 'French' for display in instrument panel

Add/remove	Code	Description
	326CK	Trailer socket for anti-skid system on frame end
	326CN	15-pin 24 V trailer socket on end of frame
	326FZ	Socket in cab 12V 2-pole and 24V 2-pole
	327AF	Battery main switch, mechanical
	329CT	Two 12-V 175-Ah batteries
	329ER	Battery box up to 175 Ah
	331CA	28V three-phase a.c. alternator 120A 3360W
	339FP	Display on the dashboard for operating data
	343AN	Acoustic warning system at end of frame for engaged reverse gear
	345AU	Maximum electronic speed limitation 89 km/h
	345EA	Cruise control
	346CA	charging pressure indicator
	350NL	Radio MAN BasicLine 24V
	352EP	2 halogen revolving beacons yellow on cab roof left and right
	362AH	Stabiliser on both rear axles
	363AA	Stabiliser for front axle
	370CM	Air dryer
	373AD	antifreeze down to -25 degrees
	376XH	Without Mattress for lower bunk
	376XK	Without Mattress for upper bunk
	376XL	No bunks for 'M', 'C', 'DK' cabs
	378XE	Without pillow
	380AC	Windscreen of laminated glass tinted
	380CA	Door windows tinted
	381AS	Cab rear wall with 2 tinted windows, centre and right
	381XC	Without curtain before bunks
	381YA	Without all-roand curtain for C/M cab
	384CD	Safety belt display, driver's side
	385AT	Side windows tinted behind B-post
	386AS	Mechanical lifting roof
	387AF	Electric door window lifters for driver and co-driver
	388AH	Roller blind for windscreen, mechanical
	388AK	Sun shade in front of windscreen
	389AC	handles left and right (on B-post)
	389AD	handles left and right (on A-post)
	390AT	Oddment box
	390CU	1 pull-out drawer in centre of dashboard

Add/remove	Code	Description
	390XN	without waste paper bins between the seats
	392AR	Kerb mirror, right, heated and electrically adjustable
	392CL	EU front mirror on co-driver's side
	392CY	Electrically heated and adjustable rear and wide-angle mirrors
	392HA	Mirror brackets for body width 2500-2600 mm width 2500 mm
	394ED	1 Fire extinguisher, Belgian, 3 kg
	400AH	mudflap front
	401CY	synthetic mudguards, 3-part, with mud flaps
	404AP	spray reducer
	405AC	Bonding set, separate
	405AK	hazard-warning sign
	405AR	Hazard-warning lamp
	407AH	Jack 12 t
	411AF	2 chocks
	417AC	wheel bolt covers front
	538AE	Plastic floor and engine tunnel covering
	542FC	anti-noise package 80 dB (92/97EEC)
	600AC	Fittings for right-hand traffic

Nationale Baugruppe

Nationale Subbaugruppe

	BE055	Transportkosten
	BE056	Voertuig in orde stellen voor technische keuring
	BE057	Voertuig aanbieden op technische keuring zonder ADR
	BE061	Ijken digitale tachograaf
	BE085	Zetelovertrekken in stof
	BE087	Vloermatten TGS Cabine
	BE091	007NF : Treingewicht 44t / P.T.R.A. 44t
	BE131	Recytyre 4-asser

Wheel

Front axle

	2 x MI 385/55R22,5 XFA2 ENGY TL
--	---------------------------------

Rear axle

	4 x MI 315/70R22,5 XMW-XD TL 154/150 L
--	--

Rear axle 2

	4 x MI 315/70R22,5 XMW-XD TL 154/150 L
--	--

Trailing axle

	2 x MI 385/55R22,5 XFA2 ENGY TL
--	---------------------------------

Add/remove Code Description

Spare tyre

1 x MI 315/70R22,5 XMW-XD TL 154/150 L

Colour

chassis

graphite black RAL 9011 matt - Water

wheels

White aluminium acrylic RAL 9006 - Normal

cab

Pure white RAL 9010 - Normal